



**NOTE**  
 1. Proximity Sensor는 Option 사양임.  
 2. Arm에 조립되는 Roller는 cylindrical type이 기본 사양임.

SPECIFICATION	
CENTERING RANGE	φ85 - φ350 mm
PISTON AREA	78 mm <sup>2</sup>
OPERATING PRESSURE	0.5-40 kgf/cm <sup>2</sup>
MAX. CLAMPING FORCE/ROLLER	2000 kgf
CENTERING ACCURACY WITHIN THE WHOLE RANGE	0.06 mm
REPEATABILITY ACCURACY	0.01 mm
MAX. ROLLER SURFACE SPEED	700 m/min
MASS APPROX.	155 kg

\* Option of central oil lubrication  
 - Oil : ISO VG68  
 - For heavy working conditions and high build up of swarf  
 - Lubrication intervals 0 - 5 min  
 - Operating pressure Min. 10 bar, Max. 40 bar  
 - The use of our separate complete lubrication unit with timer control is recommended

REV	DATE	BY	CHK	APP	QTY	ASSEMBLY
01						

  

OPERATION	DESCRIPTION	TITLE	STD.	STA-5.1	REV	NOTE
OPERATION	STEADY REST (STA-5.1)					
OPERATION	STEADY REST (STA-5.1)					

  

REV	DATE	BY	CHK	APP	QTY	ASSEMBLY
01						

